

This listing of claims will replace all prior versions, and listing of claims in the application:

Listing of claims:

Claim 1 (currently amended) A flexible container comprising opposed front and back walls sealed together proximate to their edges to define an internal space, a pair of tear-limiting strips applied to ~~a surface of, or within,~~ each wall so that the strips coincide substantially on the opposed walls, defining corresponding tear paths along each surface, wherein the strips of each pair are spaced from about 1mm to [-]2mm apart, and wherein the strips are about 1mm to about 5mm in width ~~breadth~~.

Claim 2 (original) The container of claim 1 wherein the strips of each pair are spaced from about 1.2mm to 1.8mm apart.

Claim 3 (currently amended) The container of claim 1 ~~any of the preceding claims~~ wherein the strips of each pair are ~~located to be~~ substantially parallel to each other.

Claim 4 (currently amended) The container of claim 1 ~~any one of the preceding claims~~ wherein the strips comprise sealable strips.

Claim 5 (currently amended) The container of ~~any one of claims~~ claim 1 ~~to 3~~ wherein the strips are self-adhesive.

Claim 6 (currently amended) The container of claim 1 ~~any preceding claim~~ wherein the strips are about 1.5 to [-]2.5mm in width ~~breadth~~.

Claim 7 (currently amended) The container of claim 1 ~~any one of the preceding claims~~ wherein the walls comprise a laminate material.

Claim 8 (currently amended) The container of claim 1 ~~any one of the preceding claims~~ wherein the strips are all located on ~~the~~ an outer surface of the walls.

Claim 9 (currently amended) The container of ~~any one of claim 1 to 7~~ wherein the strips are all located on ~~the~~ an inner surface of the walls.

Claim 10 (currently amended) The container of claim ~~any one of claims 1 to 7~~ wherein one pair of strips is located on an internal wall surface and ~~the other~~ another pair on an external wall surface.

Claim 11 (original) The container of claim 7 having a pair of strips located within the laminate material.

Claim 12 (original) A flexible container according to claim 1, wherein the opposed back and front walls, each have a respective top edge, the walls being sealed together proximate to the respective top edges defining an internal space between them, wherein the pair of tear-limiting strips defines a tear path located to be spaced from at least a part of the top edge thereof.

Claim 13 (currently amended) The container of claim 12, ~~wherein the~~ comprising tear barrier means ~~is manufactured from a material more tear-resistant than the material of the~~ walls.

Claim 14 (currently amended) ~~The~~ A container of claim 1 as claimed in any preceding claim wherein the tear path extends from one end to the other across the back and front walls.

Claim 15 (currently amended) ~~The~~ A container ~~as claimed in~~ of claim 12 ~~or claim 13~~ wherein the tear path extends from an end of a wall to the top edge.

Claim 16 (currently amended) ~~The~~ A container of ~~as claimed in any one of claim 12 to 15~~ wherein the ~~or each~~ pair of tear limiting strips is located between adjacent layers in a laminate wall.

Claim 17 (currently amended) A method of forming a wall material for a tearable flexible container comprising the steps of:

providing a flexible film for forming a wall of the container,

providing a tear barrier element having a substantially greater tear resistance than the wall film,

locating the element on the film to define a tear path thereon, and fixing the element to the film, and

~~wherein~~ the tear barrier element comprises a pair of tear-limiting strips which are about 1mm to about 5mm in width ~~breadth~~ and ~~wherein~~ the strips of each pair are spaced from about 1mm to 2mm apart.

Claim 18 (original) A method manufacturing a sealable bag comprising the steps of providing a flexible film and forming it into a container defining an internal space bounded by respective front and back walls, and applying a pair of tear barrier strips to the walls to define a bounded tear path on each of the front and back walls, wherein the strips are located to be spaced from about 1mm to about 2mm apart and wherein the strips are about 1mm to about 5mm in breadth.

Claim 19 (original) A method according to claim 18 comprising applying a pair of strips located to be substantially parallel to each other, the strips having substantially greater tear resistance than the flexible film.

Claim 20 (currently amended) A method of manufacturing a flexible walled container comprising the steps of providing first and second films, providing tear barrier material in strip form, applying the tear barrier material in paired strips to each film so as to define a substantially coinciding tear path on each and arranging the films in opposition to form a container comprising substantially coinciding tear paths on each wall, ~~further comprising~~ applying the paired strips so as to be spaced from about 1mm to about 2mm apart, ~~wherein~~ the strips being ~~are~~ about 1mm to about 5mm in width~~breadth~~.

Claim 21 (currently amended) A method according to claim 20 wherein the films comprise a laminate of ~~aluminum foil~~ aluminum foil and polyethylene.

Claim 22 (currently amended) A method according to claim 20-~~or~~ 21 wherein the strips comprise a tape ~~of~~ selected from the group consisting of polyester, polyethylene ~~or~~ and polypropylene.